



**Vehicle
Certification
Agency**



**Maritime &
Coastguard
Agency**



**Department
for Transport**



VCA Dangerous Goods Office
Ashcombe House
5 The Crescent, Leatherhead
Surrey, KT22 8DY, UK
T +44 (0)1372 226110
E dgenquiries@vca.gov.uk

www.vehicle-certification-agency.gov.uk

CERTIFICATE OF PACKAGING PERFORMANCE

Issued on behalf of the Department for Transport, Civil Aviation Authority and the Maritime and Coastguard Agency by the VCA Dangerous Goods Office

Certificate serial number: **7681**

NOT TRANSFERABLE

Application No.: **10542**

Issue number and date: **01 28/05/2025**

Issued to:
MAUSER UK LTD
Unit 3 Greenvale Business Park
Todmorden Road
Littleborough
Greater Manchester
OL15 9AZ

Packaging type: **3H2W**

Description:

**Jerrican, plastics, removable head,
equivalent packaging**

Capacity: **60 litres** Height: **652 mm.**
Section dimensions: **404 length x 333 width**
Full aperture: **Yes** Closing ring:

Bodymass: **1.304 Kg** Tare: **1.637 kg**

Handle: **2 x INTEGRAL HANDLES ON BODY**

Head gasket:

CLOSURES: No in Head: **1** No in Body: **0**

Contents: **Tested with Anti-Freeze Wetted Nappies & Printer's Cloth for
Clinical Waste**

Plastics	
Size:	394X328mm
Type:	
Push Fit Plastics Lid with -18 captive lugs	
Maker:	
MAUSER	
Overcap: ☐	
Washer/wad and Closure Torque	
Foam	Nm
	Nm

Special Notes:

Contains LDPE 40 micron - 1060 x 620mm Outer Plastics Bag and 1060 x 620mm Inner bag P622 refers.

UN 6.1.1.2 and in accordance with UN 4.1.1.15 the GB competent authority restricts the use to 2 years from date of manufacture.

Additional options and chemical compatibility in schedule issue no n/a dated n/a.

It is certified that samples of the packaging design type described above have been tested in accordance with the provisions of the United Nations Recommendations on the Transport of Dangerous Goods, Chapter 6.1 (and the equivalent provisions in RID/ADR, the IMDG Code and the ICAO Technical Instructions) and successfully met the criteria described in paragraphs 6.1.5.3 to 6.1.5.6:

To test levels of:

The packaging is approved, as provided in the relevant transport rule, to contain solids of:

DROP HEIGHT (m) **1.8** packing group **density (d)** gross mass (kg)

15

STACKED AT 3m with RD (d)

II

III

THE TEST REPORT(S) AND ITS APPENDICES ARE AN INTEGRAL PART OF THIS DOCUMENT

Packagings of the sample specifications shall bear the marking:

(H) 3H2W/X15/S//GB/7681**

**** To be replaced by the last two
digits of the year of manufacture**

Revalidation due by: 31/12/2030

For further details see www.vca.gov.uk

Signed:

[Signature]

for Ziyad Akhlaq. Head of Dangerous Goods VCA DGO