



Vehicle
Certification
Agency



Maritime &
Coastguard
Agency



Department
for Transport



VCA Dangerous Goods Office
Wesley House
Bull Hill, Leatherhead
Surrey, KT22 7AH, UK
T +44 (0)1372 226110
E dgenquiries@vca.gov.uk
www.vehicle-certification-agency.gov.uk

CERTIFICATE OF PACKAGING PERFORMANCE

Issued on behalf of the Department for Transport, Civil Aviation Authority and the Maritime and Coastguard Agency by the VCA Dangerous Goods Office

Certificate serial number: 7425

NOT TRANSFERABLE

Application No.: 10085

Issue number and date: 01 10/08/2022

Issued to: MAUSER UK LTD
Unit 3 Greenvale Business Park
Todmorden Road
Littleborough
Greater Manchester
OL15 9AZ

Packaging type: 3H2W

Description:

Jerrican, plastics, removable head,
equivalent packaging

Capacity: 60 litres	Height: 646 mm.	Body mass: 1.39 Kg	Tare: 1.68 kg
Section dimensions: 400 length x 334 width	Handle: 2 off to base of closure	Head gasket: Flowed in adhesive	
Full aperture: Yes Closing ring:	Contents: Tested with wetted nappies, printers cloths and sharps bins, for clinical waste.		
CLOSURES: No in Head: 0 No in Body: 0			

P622 refers. Intermediate packaging is a clinical waste bag, containing an inner clinical waste bag. Optionally, contents may include up to 2x 5-litre approved plastics sharps bins, each of max gross mass 1kg, double-bagged and placed in base of outer. Any bag may be used which has passed the tests for bulk transport defined in 7.3.2.6.2 (c) and 4.3.2.4.2.3 (IMDG Code); each must be closed as per the respective bag approval. Gross mass of the filled packaging in use must comply with the permitted gross mass for each bag as well as for the overall packaging.
Not to be used for sharps except as described.

Special Notes:

Viva60. Post consumer recycled polymer. Approval issued in accordance with UN 6.1.1.2 and in accordance with UN 4.1.1.15 the GB competent authority restricts the use to 2 years from date of manufacture.

Additional options and chemical compatibility in schedule issue no n/a dated n/a.

It is certified that samples of the packaging design type described above have been tested in accordance with the provisions of the United Nations Recommendations on the Transport of Dangerous Goods, Chapter 6.1 (and the equivalent provisions in RID/ADR, the IMDG Code and the ICAO Technical Instructions) and successfully met the criteria described in paragraphs 6.1.5.3 to 6.1.5.6:

To test levels of:	The packaging is approved, as provided in the relevant transport rule, to contain solids of:		
DROP HEIGHT (m)	1.8	packing group	gross mass (kg)
		I	15
STACKED AT 3m with RD (d)	-	II	15
		III	15

THE TEST REPORT(S) AND ITS APPENDICES ARE AN INTEGRAL PART OF THIS DOCUMENT

Packagings of the sample specifications shall bear the marking:

Ⓢ 3H2W/X15/S/**/GB/7425

** To be replaced by the last two digits of the year of manufacture

Revalidation due by: 31/12/2027

For further details see www.vca.gov.uk

Signed:

Keith F B White. Head of Dangerous Goods VCA DGO